

Naaldhulslager NBXI5040Z-IKO - NBXI5040Z-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nbxi5040z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number

Shaft dia. mm	Mass (Ref.) g		Mass (Ref.) g		Mass (Ref.) g		d	D	D _i
	With dust cover	Without dust cover	With dust cover	Without dust cover	With dust cover	Without dust cover			
50	---	---	---	---	---	---	50	72	85

Identification number: **NBXI 5040Z**

Boundary dimensions mm				Bore chamfer mm	Bore chamfer mm	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring				
D ₂	L	B	H			Radial	Axial	Radial	Axial						
86.5	40	25.5	17	12	1	1	60	82	59	47 500	64 600	103 000	224 000	4 000	LRT 506025

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.

Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952391076
Binnendiameter	50 mm
Buitendiameter	72 mm
Dikte	40 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE