

Naaldhulslager

NAXI6040-IKO - NAXI6040-IKO


<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/naxi6040-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing
Needle Roller Bearings with Thrust Roller Bearing

With Inner Ring
With Inner Ring



Identification number											
Shaft dia. mm		Mass (Ref.) g	With dust cover	Mass (Ref.) g		Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D ₁
60	NAXI 6040	750							60	85	95

Boundary dimensions mm				Load capacity mm		Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 607025								
D ₂	L	B	H	I ₁	I ₂	Radial	axial	Radial	axial										
96.5	40	25.5	18	11	1	70	85	68	55	500	43	100	120	000	101	000	3	500	LRT 607025

Notes⁽¹⁾

(1) Minimum allowable value of chamfer dimension r

(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remark 1: The outer ring has an oil groove and an oil hole.

2: Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952391083
Binnendiameter	60 mm
Buitendiameter	85 mm
Dikte	40 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE