


GE Stangkop SB110A-IKO - SB110A-IKO

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/sb110a-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree α
			d	D	B	C	d_k	r_1 mm ⁽¹⁾	
110	SB 110A	8,95	110	170	93	80	160	1	5
Mounting dimensions mm		Dynamic load capacity C_d N	Static load capacity C_s N	d_s		D_s			
Min.	Max. ⁽²⁾			Min.	Max.	Min.	Max.	Min.	Max.
115.5	130	164.5	149	1 260 000	7 530 000				

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark1: The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2: Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952391540
Binnendiameter	110 mm
Buitendiameter	170 mm
Dikte	93 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE