


GE Stangkop GE90ES-IKO - GE90ES-IKO

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/ge90es-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d _s	r ₁ ⁽¹⁾ r _{1a} min.	r ₂ ⁽¹⁾ r _{2a} min.	α	α ₁
90	GE 90ES		2.82	90	130	60	50	115	1	1	5	3
Mounting dimensions mm		Dynamic load capacity C _d		Static load capacity C _s								
d _s		D _s		N		N						
Min.	Max. ⁽²⁾	Max.	Min.									
95.5	98	124.5	112	564 000		3 380 000						

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
 Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
 2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952391946
Binnendiameter	90 mm
Buitendiameter	130 mm
Dikte	60 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE