

GE Stangkop


GE100ES-2RS-IKO - GE100ES-2RS-IKO

https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/ge100es-2rs-iko

IKO

SPHERICAL BUSHINGS

Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degrees		
	Without seals	With seals		A	D	B	C	d _s	r ₁ (1)	r ₂ (1)	α	α _l
100		GE 100ES-2RS	4.43	100	150	70	55	130	1	1	7	5
Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N									
d _s	D _s											
Min.	Max.(2)	Min.										
105.5	109.5	144.5	127	701 000	4 210 000							

Notes(1)

(1) Minimum allowable value of chamfer dimensions r₁ and r₂

(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.

Remark(1)

The inner ring and the outer ring have an oil groove and two oil holes, respectively.

2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952391960
Binnendiameter	100 mm
Buitendiameter	150 mm
Dikte	70 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.be
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE