

GE Stangkop GE260ES-2RS-IKO - GE260ES-2RS-IKO

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/ge260es-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1	
260		GE 260ES-2RS	52.0	260	370	150	110	325	1.1	1.1	7	6	
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s									
d_s	D_s												
Min.	Max.(2)	Max.	Min.	N		N							
267	288	363	320	3 510 000		21 000 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392134
Binnendiameter	260 mm
Buitendiameter	370 mm
Dikte	150 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE