


GE Stangkop GE280ES-IKO - GE280ES-IKO

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/ge280es-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1	
280	GE 280ES		66.0	280	400	155	120	350	1.1	1.1	6	5	
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s									
d_s		D_s		N		N							
Min.	Max.(2)	Max.	Min.										
287	313.5	393	345	4 120 000		24 700 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392158
Binnendiameter	280 mm
Buitendiameter	400 mm
Dikte	155 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE