


GE Stangkop GE110GS-IKO - GE110GS-IKO

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/ge110gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
110	GE 110GS		9,70	110	180	100	70	160	1	1	12	11
Mounting dimensions mm			Dynamic load capacity C_d N	Static load capacity C_s N								
d_s	D_s				Min.	Max.(2)	Min.	Max.	Min.	Max.	Min.	Max.
115.5	124.5	174.5	154	1 100 000	6 590 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392516
Binnendiameter	110 mm
Buitendiameter	180 mm
Dikte	100 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE