

## GE Stangkop GE110GS-2RS-IKO - GE110GS-2RS-IKO

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/ge110gs-2rs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		$d$	$D$	$B$	$C$	$d_s$	$r_1$ (1)	$r_2$ (1)	$\alpha$	$\alpha_1$
<b>110</b>		<b>GE 110GS-2RS</b>	<b>9.70</b>	<b>110</b>	<b>180</b>	<b>100</b>	<b>70</b>	<b>160</b>	<b>1</b>	<b>1</b>	<b>12</b>	<b>11</b>
Mounting dimensions mm		Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N	$d_s$		$D_s$						
Min.	Max. (2)			Max.	Min.	Max.	Min.	Max.				
115.5	124.5	174.5	154	1 100 000	6 590 000							

Notes (1) Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392523
Binnendiameter	110 mm
Buitendiameter	180 mm
Dikte	100 mm
Type	GE
Smering	zonder
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE