

# GE Stangkop

## GE260GS-2RS-IKO - GE260GS-2RS-IKO

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/ge260gs-2rs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		$d$	$D$	$B$	$C$	$d_s$	$r_1$ (1)	$r_2$ (1)	$\alpha$	$\alpha_1$	
<b>260</b>		<b>GE 260GS-2RS</b>	81,8	260	400	205	120	350	1,1	1,1	15	14	
Mounting dimensions mm		Dynamic load capacity $C_d$		Static load capacity $C_s$									
$d_s$		$D_s$		N		N							
Min.	Max.(2)	Min.	Max.	N		N							
267	283,5	393	345	4 120 000		24 700 000							

Notes (1) Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark: The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392684
Binnendiameter	260 mm
Buitendiameter	400 mm
Dikte	205 mm
Type	GE
Smering	zonder
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE