

GE Stangkop GE280GS-2RS-IKO - GE280GS-2RS-IKO

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/ge280gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
280		GE 280GS-2RS	97,4	280	430	210	120	375	1,1	1,1	15	14
Mounting dimensions mm			Dynamic load capacity C_d N	Static load capacity C_s N								
d_s	D_s				Min.	Max. (2)	Min.	Max.	Min.	Max.	Min.	Max.
287	310,5	423	371	4 410 000	26 500 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392691
Binnendiameter	280 mm
Buitendiameter	430 mm
Dikte	210 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE