


## GE Stangkop SBB56-2RS-IKO - SBB56-2RS-IKO

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/sbb56-2rs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings Inch Series



Shaft dia. mm (inch)	Identification number		Mass (flat) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
<b>88.900</b> (3 1/2)		<b>SBB 56-2RS</b>	<b>4.83</b>	88.900 (3 1/2)	139.700 (5 1/2)	77.77 (3.062)	66.68 (2.625)
Radial internal clearance mm Min./Max.	Mounting dimensions mm		Dynamic load capacity C <sub>d</sub> N	Static load capacity C <sub>s</sub> N			
	d <sub>k</sub>	d <sub>1</sub>		r <sub>1</sub> max. Min.	r <sub>2</sub> max. Min.		
128(5.039)	0.13 / 0.23	101.6	0.6	0.8	837 000	5 020 000	

Notes: (1) Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>k</sub>.  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392974
Binnendiameter	88.9 mm
Buitendiameter	139.7 mm
Dikte	77.77 mm
Type	GE
Smering	zonder
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE