


## GE Stangkop SBB96-IKO - SBB96-IKO

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/sbb96-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
<b>152.400</b> (6)	<b>SBB 96</b>		<b>17.6</b>	152.400 (6)	222.250 (8 7/8)	120.65(4.750)	104.78(4.125)
Radial internal clearance mm Min./Max.	Mounting dimensions mm		Dynamic load capacity C <sub>d</sub> N	Static load capacity C <sub>s</sub> N			
	d <sub>k</sub>	d <sub>1</sub> r <sub>1</sub> max. r <sub>2</sub> max.		r <sub>1</sub> min. r <sub>2</sub> min.			
207(8.150)	0.13 / 0.23	167.5	0.8	1.1	2 130 000	12 800 000	

Notes: (1) Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>k</sub>.  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952393100
Binnendiameter	152.4 mm
Buitendiameter	222.25 mm
Dikte	120.65 mm
Type	GE
Smering	zonder
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE