


GE Stangkop GE60EC-2RS-IKO - GE60EC-2RS-IKO

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/ge60ec-2rs-iko>

IKO
SPHERICAL BUSHINGS
Maintenance-free Spherical Bushings



| Shaft dia. mm | Identification number | | Mass (Ref.) kg | Boundary dimensions mm | | | | | | Permissible tilting angle degree | | |
|---------------------------|-----------------------|--------------------|--|---------------------------|---|---------|----|----------------|----------------------------------|--|---|----------------|
| | Without seals | With seals | | d | D | B | C | d _k | r ₁ mm ⁽¹⁾ | r ₂ mm ⁽¹⁾ | α | α ₁ |
| 60 | — | GE 60EC-2RS | 1,10 | 60 | 90 | 44 | 36 | 80 | 1 | 1 | — | 3 |
| Mounting dimensions mm | | | Dynamic load capacity C _d | | Static load capacity C _s | | | | | | | |
| d _s | | D _s | | N | | N | | | | | | |
| Min. | Max. ⁽²⁾ | Max. | Min. | N | | N | | | | | | |
| 65.5 | 66.5 | 84.5 | 79 | 282 000 | | 706 000 | | | | | | |

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark No oil hole is provided.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3663952393223 |
| Binnendiameter | 60 mm |
| Binnendiameter | 2.362" inch |
| Buitendiameter | 90 mm |
| Buitendiameter | 3.543" inch |
| Dikte | 44 mm |
| Dikte | 1.732" inch |
| Type | GE |
| Smering | zonder |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE