

# Kegellager 33124-JR-JTEKT - 33124-JR-KOYO

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegellager/33124-jr-koyo>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)              |                    |                          |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |                      | Bearing No. <sup>1)</sup> |                    |                |                      |      |
|---------------------------------------|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|------|
| d                                     | D                  | T                        | B                    | C                       | r <sub>1</sub>       | r <sub>2</sub>       | C <sub>r</sub>       | C <sub>0r</sub>                      | Grease lub.          |                           | Oil lub.           |                |                      |      |
| 120                                   | 200                | 62                       | 62                   | 48                      | 2.5                  | 2                    | 482                  | 785                                  | 1 800                | 2 400                     | 33124JR            |                |                      |      |
| Dimension series to ISO955 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                         |                      |                      |                      |                                      |                      | Constant e                | Axial load factors |                | (Refer. 1) Mass (kg) |      |
|                                       |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | D <sub>1a</sub> min.    | D <sub>1a</sub> max. | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>1a</sub> min.                 | r <sub>1a</sub> max. |                           | Y <sub>1</sub>     | Y <sub>0</sub> |                      |      |
| 3FE                                   | 47.8               | 132                      | 133                  | 190                     | 172                  | 192                  | 9                    | 14                                   | 2                    | 2                         | 0.40               | 1.51           | 0.83                 | 7.73 |

## PRODUCTKENMERKEN

|                |               |
|----------------|---------------|
| Merk           | JTEKT         |
| N° Ean13       | 3663952411385 |
| Binnendiameter | 120 mm        |
| Buitendiameter | 200 mm        |
| Dikte          | 62 mm         |
| Verpakking     | 1             |

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE