


# Nokrollen CFE16-IKO - CFE16-IKO

<https://www.123kogellager.be/kogellager-behuizing/kogellager/nokrollen/cfe16-iko>

IKO

## CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		$\emptyset$	D	C	$d_2$
22	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	190	35	18	22
	<b>CFE 16</b>							

Boundary dimensions mm										Essentiality	Mounting dimension $f$ Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating $C_0$ N	Maximum allowable static load N
G	$B_3$	$B$ max	$B_1$ max	$B_2$	$C_1$	$G_1$	$r_{max}$	$r_{min}$	$e$						
M16×1.5	15.5	19.6	52.1	32.5	0.8	6	17	0.6	0.8	26	58.5	12 000	18 300	18 300	

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060459978
Binnendiameter	22 mm
Buitendiameter	35 mm
Dikte	18 mm
Gewicht	190 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE