

# Nokrollen


## CFE24-1-UUR-IKO - CFE24-1-UUR-IKO

<https://www.123kogellager.be/kogellager-behuizing/kogellager/nokrollen/cfe24-1-uur-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		$\emptyset$	D	C	$d_2$
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
33				CFE 24-1 UUR	1 220	72	29	33

Boundary dimensions mm										Essentiality	Mounting dimension $f$ Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating $C_0$ N	Maximum allowable static load N
G	$B_3$	$B$ max	$B_1$ max	$B_2$	$C_1$	$G_1$	$r_{max}$	$r_{min}$	$r$						
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	1	0.8	40	215	30 500	52 600	52 000	

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060460165
Binnendiameter	33 mm
Buitendiameter	72 mm
Dikte	29 mm
Gewicht	1220 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE