

Nokrollen

CFE18-VUUR-IKO - CFE18-VUUR-IKO

https://www.123kogellager.be/kogellager-behuizing/kogellager/nokrollen/cfe18-vuur-iko

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers

Full Complement Type/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.) g	D	C	d _a
	Shield type		Sealed type					
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
24			CFE 18	VUUR	285	40	20	24

Boundary dimensions mm										
G	B ₃	B _{max}	B ₁ max	B ₂	C ₁	g ₁	G ₁	r ₁ min	Eccentricity E	Mounting dimension f Min. mm
M18 X 1.5	17.5	21.6	58.1	36.5	0.8	6	19	1	0.8	29

Maximum aligning torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀	Maximum allowable static load
N-m	N	N	N
86.2	25 300	51 300	31 100

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060461155
Binnendiameter	24 mm
Buitendiameter	40 mm
Dikte	20 mm
Gewicht	285 g
Verpakking	1

contact@123kogellager.be
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE