

Nokrollen CFE24-1-VUUR-IKO - CFE24-1-VUUR-IKO

<https://www.123kogellager.be/kogellager-behuizing/kogellager/nokrollen/cfe24-1-vuur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
33	CFE 24-1 VUUR				1 220	72	29	33

Boundary dimensions mm														
G	B ₃	B _{max}	B ₁ _{max}	B ₂	C ₁	g ₁	G ₁	r ₁ ⁽¹⁾ _{min}	Excentricity E	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M24 × 1.5	25.5	30.6	80.1	49.5	0.8	8	24	1	0.8	40	215	46 800	92 000	52 000

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060461285
Binnendiameter	33 mm
Buitendiameter	72 mm
Dikte	29 mm
Gewicht	1220 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE