


## Nokrollen CFE30-V-IKO - CFE30-V-IKO

<https://www.123kogellager.be/kogellager-behuizing/kogellager/nokrollen/cfe30-v-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



Outside diameter of eccentric collar mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		g	D	C	d <sub>e</sub>						
41	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	2 030	80	35	41						
<b>CFE 30 V</b>														
Boundary dimensions mm														
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>1</sub> <sub>max</sub>	B <sub>2</sub>	C <sub>1</sub>	g <sub>1</sub>	G <sub>1</sub>	r <sub>1</sub> <sub>min</sub> (°)	Eccentricity E	Mounting diameter f Min.	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
M30 × 1.5	32.5	37	100	63	1	8	30.5	1	1.5	49	438	67 700	144 000	85 900

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060461315
Binnendiameter	41 mm
Binnendiameter	1.614" inch
Buitendiameter	80 mm
Buitendiameter	3.15" inch
Dikte	35 mm
Dikte	1.378" inch
Gewicht	2030 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE