

Nokrollen CR16-UU-IKO - CR16-UU-IKO

<https://www.123kogellager.be/kogellager-behuizing/kogellager/nokrollen/cr16-uu-iko>



CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)	g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
11.112 ($\frac{7}{16}$)	CR 16 UU				73	25.400	15.875	11.112	$\frac{5}{16}$ -20	12.700	
Boundary dimensions mm(inch)											
B max	B ₂	B ₃	C ₁	S ₁	S ₂	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C	Basic dynamic load rating C	Basic static load rating C ₀	
17.3 (0.68)	25.400 (1)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{16}$)	4.702 ($\frac{3}{16}$)	3.175 ($\frac{1}{8}$)	1.191 ($\frac{1}{8}$)	17.859 ($\frac{5}{8}$)	17.4	8 910	10 800	

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060462930
Binnendiameter	11.112 mm
Buitendiameter	25.4 mm
Dikte	15.875 mm
Gewicht	73 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE