


## Nokrollen CR18-IKO - CR18-IKO

<https://www.123kogellager.be/kogellager-behuizing/kogellager/nokrollen/cr18-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



| Stud dia.<br>mm<br>(inch)    | Identification number      |                                |                            |                                | Mass<br>(Ref.)          | g                        | D   | C                                    | d <sub>1</sub>                                 | G<br>UNF                                      | G <sub>1</sub> |
|------------------------------|----------------------------|--------------------------------|----------------------------|--------------------------------|-------------------------|--------------------------|---|--------------------------------------|--|---|----------------|
|                              | Shield type                |                                | Sealed type                |                                |                         |                          |   |                                      |  |   |                |
|                              | With covered<br>outer ring | With cylindrical<br>outer ring | With covered<br>outer ring | With cylindrical<br>outer ring |                         |                          |   |                                      |  |   |                |
| 11.112<br>( $\frac{7}{16}$ ) | CR 18                      |                                |                            |                                | 88                      | 28.575 ( $\frac{1}{1}$ ) | 15.875 ( $\frac{1}{2}$ )                      | 11.112 ( $\frac{1}{2}$ )             | $\frac{1}{8}$ -20                              | 12.700 ( $\frac{1}{2}$ )                      |                |
| Boundary dimensions mm(inch) |                            |                                |                            |                                |                         |                          |   |                                      |  |   |                |
| B<br>max                     | B <sub>2</sub>             | B <sub>3</sub>                 | C <sub>1</sub>             | S <sub>1</sub>                 | S <sub>2</sub>          | r                        | Bearing<br>dimension<br>f<br>Min.<br>mm(inch) | Maximum<br>tightening<br>torque<br>C | Basic dynamic<br>load rating<br>C <sub>0</sub> | Basic static<br>load rating<br>C <sub>0</sub> |                |
| 17.3 (0.68)                  | 25.400 (1)                 | 6.350 ( $\frac{1}{4}$ )        | 0.794 ( $\frac{1}{32}$ )   | 4.762 ( $\frac{3}{16}$ )       | 3.175 ( $\frac{1}{8}$ ) | 1.588 ( $\frac{1}{16}$ ) | 19.050 ( $\frac{3}{4}$ )                      | 17.4                                 | 9 180  | 11 600  |                |

## PRODUCTKENMERKEN

|                |               |
|----------------|---------------|
| Merk           | IKO           |
| N° Ean13       | 3616060462954 |
| Binnendiameter | 11.112 mm     |
| Buitendiameter | 28.575 mm     |
| Dikte          | 15.875 mm     |
| Gewicht        | 88 g          |
| Verpakking     | 1             |

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE