


## Nokrollen CR26-IKO - CR26-IKO

<https://www.123kogellager.be/kogellager-behuizing/kogellager/nokrollen/cr26-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



| Stud dia.<br>mm<br>(inch)    | Identification number      |                                |                            |                                | Mass<br>(Ref.)<br>g | D              | C   | d <sub>1</sub>                       | G<br>UNF                                       | G <sub>1</sub>                                |
|------------------------------|----------------------------|--------------------------------|----------------------------|--------------------------------|---------------------|----------------|---|--------------------------------------|--|---|
|                              | Shield type                |                                | Sealed type                |                                |                     |                |   |                                      |  |   |
|                              | With covered<br>outer ring | With cylindrical<br>outer ring | With covered<br>outer ring | With cylindrical<br>outer ring |                     |                |   |                                      |  |   |
| 15.875<br>(5/8)              | CR 26                      |                                |                            |                                | 260                 | 41.275 (1 1/2) | 22.225 (7/8)                                  | 15.875 (5/8)                         | G <sub>1</sub> -18                             | 19.050 (3/4)                                  |
| Boundary dimensions mm(inch) |                            |                                |                            |                                |                     |                |   |                                      |  |   |
| B <sub>max</sub>             | B <sub>2</sub>             | B <sub>3</sub>                 | C <sub>1</sub>             | δ <sub>1</sub>                 | δ <sub>2</sub>      | r              | Bearing<br>dimension<br>f<br>Min.<br>mm(inch) | Maximum<br>tightening<br>torque<br>C | Basic dynamic<br>load rating<br>C <sub>0</sub> | Basic static<br>load rating<br>C <sub>0</sub> |
| 23.8 (9/16)                  | 38.100 (1 1/2)             | 9.525 (3/8)                    | 0.794 (1/16)               | 4.702 (3/16)                   | 3.969 (1/8)         | 1.588 (1/16)   | 26.199 (1 1/16)                               | 55.7                                 | 10 800   | 24 300  |

## PRODUCTKENMERKEN

|                |               |
|----------------|---------------|
| Merk           | IKO           |
| N° Ean13       | 3616060463005 |
| Binnendiameter | 15.875 mm     |
| Buitendiameter | 41.275 mm     |
| Dikte          | 22.225 mm     |
| Gewicht        | 260 g         |
| Verpakking     | 1             |

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE