


Nokrollen CR26-UUR-IKO - CR26-UUR-IKO

<https://www.123kogellager.be/kogellager-behuizing/kogellager/nokrollen/cr26-uur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
15.875 (5/8)			CR 26	UUR	260	41.275 (1 5/8)	22.225 (7/8)	15.875 (5/8)	G ₁ -18	19.050 (3/4)
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	
B max	B ₂	B ₃	C ₁	δ ₁	δ ₂					r
23.8 (9.37)	38.100 (1 1/2)	9.525 (3/8)	0.794 (1/32)	4.702 (3/16)	3.969 (1/8)	1.588 (1/16)	26.199 (1 1/8)	55.7	19 800	24 300

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060463012
Binnendiameter	15.875 mm
Binnendiameter	5/8" inch
Buitendiameter	41.275 mm
Buitendiameter	1 5/8" inch
Dikte	22.225 mm
Dikte	7/8" inch
Gewicht	260 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE