


## Naaldhulslager 32BTM4025PL-JTEKT - 32BTM4025PL-KOYO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/32btm4025pl-koyo>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	Oil lub.	Caged type With open ends    With closed end
32	40	25	—	27.8	50.8	11 000 <b>32BTM4025PL</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (F6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	31.984	32.000	39.989 <sup>4)</sup>	40.014 <sup>4)</sup>	57	—

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952472058
Binnendiameter	32 mm
Buitendiameter	40 mm
Dikte	25 mm
Gewicht	57 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE