

## Naaldhulslager 36BTM4824-JTEKT - 36BTM4824-KOYO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/36btm4824-koyo>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type	
							With open ends	With closed end
36	48	24	—	33.2	48.7	9 800	36BTM4824	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6)		Housing bore dia. (N7)		With open ends	With closed end
		min.	max.	min.	max.		
—	—	35.984	36.000	47.967	47.992	95	—

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952472386
Binnendiameter	36 mm
Buitendiameter	48 mm
Dikte	24 mm
Gewicht	95 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE