


Naaldtaatslager AZ13017030-IKO - AZ13017030-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldtaatslager/az13017030-iko>

IKO

THRUST BEARINGS

Thrust Roller Bearings



Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
130	AZ 13017030	2 180	AZK 13017012	860	WS 130170	GS 130170	660

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d ₄ Min.	D ₄ Max.	N	N	rpm
130	170	30	130.1	169.5	12	9	1	140	164	163	140	176 000	741 000	2 000

Notes: (*) Minimum allowable value of chamfer dimension r
(1) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060466495
Binnendiameter	130 mm
Buitendiameter	170 mm
Dikte	30 mm
Gewicht	2180 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE