


Naaldtaatslager AZ17023045-IKO - AZ17023045-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldtaatslager/az17023045-iko>

IKO

THRUST BEARINGS

Thrust Roller Bearings



Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
170	AZ 17023045	6 220	AZK 17023019	2 420	WS 170230	GS 170230	1 900

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d ₄ Min.	D ₄ Max.	N	N	rpm
170	230	45	170.1	229	19	13	1.5	183	221	220	184	406 000	1 730 000	1 500

Notes: (*) Minimum allowable value of chamfer dimension r
(1) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060466600
Binnendiameter	170 mm
Buitendiameter	230 mm
Dikte	45 mm
Gewicht	6220 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE