


Sluitring GS60130-IKO - GS60130-IKO

<https://www.123kogellager.be/accessoires/ringen/sluitring/g60130-iko>

IKO

THRUST BEARINGS

Thrust Roller Bearings



Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
60	AZ 6013026	2 090	AZK 6013010	790	WS 60130	GS 60130	660

Boundary dimensions mm										Standard mounting dimensions mm	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾	
d	D	T	d _c	D _c	D _w	B	r _{s,mini} ⁽¹⁾	C ₁	C ₂	d _s Min.	D _s Max.	N	N	rpm
60	130	26	60.05	129.5	10	8	1.5	79	119	119	80	158 000	634 000	3 000

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060466860
Binnendiameter	60 mm
Buitendiameter	130 mm
Dikte	8 mm
Materiaal	STAAL
Gewicht	650 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE