


Sluitring GS160200-IKO - GS160200-IKO

<https://www.123kogellager.be/accessoires/ringen/sluitring/gs160200-iko>

IKO

THRUST BEARINGS

Thrust Roller Bearings



Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
160	AZ 16020031	2 710	AZK 16020012	1 030	WS 160200	GS 160200	840

Boundary dimensions mm										Standard mounting dimensions mm	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾	
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d _s Min.	D _s Max.	N	N	rpm
160	200	31	160.1	199.5	12	9.5	1	170	194	193	170	189 000	895 000	1 700

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060467225
Binnendiameter	160 mm
Buitendiameter	200 mm
Dikte	9.5 mm
Materiaal	STAAL
Gewicht	840 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE