

Sluitring WS190255-IKO - WS190255-IKO

<https://www.123kogellager.be/accessoires/ringen/sluitring/ws190255-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings

| Shaft dia. mm | Identification number | | | | | | |
|---------------|-----------------------|---------------|-----------------------|---------------|------------|------------|---------------|
| | Thrust roller bearing | Mass (Ref.) g | Thrust roller bearing | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g |
| 190 | AZ 19025548 | 8 080 | AZK 19025520 | 3 100 | WS 190255 | GS 190255 | 2 480 |

| Boundary dimensions mm | | | | | | | | | | Standard mounting dimensions mm | | Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ |
|------------------------|-----|----|----------------|----------------|----------------|----|--------------------|----------------|----------------|---------------------------------|---------------------|-----------------------------|---|---|
| d | D | T | d _c | D _c | D _w | B | r _s (1) | C ₁ | C ₂ | d ₄ Min. | D ₄ Max. | N | N | rpm |
| 190 | 255 | 48 | 190.1 | 254 | 20 | 14 | 2 | 205 | 245 | 244 | 206 | 470 000 | 2 080 000 | 1 300 |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3616060467331 |
| Binnendiameter | 190 mm |
| Buitendiameter | 255 mm |
| Dikte | 14 mm |
| Materiaal | STAAL |
| Gewicht | 2480 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE