


Sluitring GS200340-IKO - GS200340-IKO

<https://www.123kogellager.be/accessoires/ringen/sluitring/gs200340-iko>

IKO

THRUST BEARINGS

Thrust Roller Bearings



Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
200	AZ 20034039	17 200	AZK 20034015	6 120	WS 200340	GS 200340	5 540

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d _s Min.	D _s Max.	N	N	rpm
200	340	39	200.15	338	15	12	4	227	323	322	228	7 10 000	4 580 000	1 100

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060467409
Binnendiameter	200 mm
Buitendiameter	340 mm
Dikte	12 mm
Materiaal	STAAL
Gewicht	5540 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE