

## SI Stangkop DSIL5-T-K-DURBAL - DSIL5-T-K-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/dsil5-t-k-durbal>


### DSIL5-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



rod end body:  
surface zinc plated

sliding combination:  
steel / bronze-PTFE composite

inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

outer ring:  
brass body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
maintenance free

order number	right hand thread	left hand thread	measurement (mm)						
DSIL 5 T/K	5	M 5	8	6,00	18	8,5	11		

type	measurement (mm)			load rating C <sub>0</sub> (N)	weight (kg)
	l <sub>1</sub> min	W	h		
DSI / DSIL 5 T/K	10	9	27	6,0	0,016

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952489070
Binnendiameter	5 mm
Buitendiameter	18 mm
Dikte	8 mm
Type	SI
Gewicht	16 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE