

SI Stangkop SIL6-T-K-DURBAL - SIL6-T-K-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/sil6-t-k-durbal>


SIL6-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SIL 6 T/K		6	M 6	9	6,75	20	10,0	13

type	measurement [mm]			h	d ₁	load rating C ₀ [N]	weight [kg]
	l ₁ min	W					
SI / SIL 6 T/K	12	11		30	13	7,7	0,022

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952489117
Binnendiameter	6 mm
Buitendiameter	20 mm
Dikte	9 mm
Type	SI
Gewicht	22 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE