

## SI Stangkop SIL12-T-K-DURBAL - SIL12-T-K-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/sil12-t-k-durbal>


### SIL12-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
	SIL 12 T/K	12	M 12	16	12,00	32	17,5	22

type	measurement [mm]			load rating C <sub>10</sub> [N]	weight [kg]
	l <sub>1</sub> min	W	h		
SI / SIL 12 T/K	22	19	50	24,0	0,100

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952489261
Binnendiameter	12 mm
Buitendiameter	32 mm
Dikte	16 mm
Type	SI
Gewicht	100 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE