

SI Stangkop SI22-T-K-DURBAL - SI22-T-K-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/si22-t-k-durbal>


SI22-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

| order number | right hand thread | left hand thread | measurement [mm] | | | | | | |
|--------------|-------------------|------------------|------------------|------------|----|----------------|----------------|----------------|----------------|
| SI 22 TIK | | | d | G | B | C ₁ | d ₂ | d ₃ | d ₄ |
| | | | 22 | M 22 x 1,5 | 28 | 20,00 | 54 | 30,0 | 38 |

| type | measurement [mm] | | | d PT | load rating C ₁₀ [N] | weight [kg] |
|-----------------|--------------------|----|----|---------|---------------------------------------|----------------|
| | l ₁ min | W | h | | | |
| SI / SIH 22 TIK | 37 | 32 | 84 | 15 | 68,0 | 0,540 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | DURBAL |
| N° Ean13 | 3663952489605 |
| Binnendiameter | 22 mm |
| Buitendiameter | 54 mm |
| Dikte | 28 mm |
| Type | SI |
| Gewicht | 540 g |
| Draad | Rechtse draad |
| Smering | zonder |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE