

SI Stangkop SIL40-T-K-DURBAL - SIL40-T-K-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/sil40-t-k-durbal>


SIL40-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement [mm]
right hand thread	d G B C1 d2 d3 d4
left hand thread	
SIL 40 T/K	40 M 42 x 2 49 33,00 91 53,0 65

type	measurement [mm]			load rating C ₅ [kN]	weight [kg]
	l ₃ min	W	h		
SI / SIL 40 T/K	60	55	142	17	2,400

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952489810
Binnendiameter	40 mm
Buitendiameter	91 mm
Dikte	49 mm
Type	SI
Gewicht	2400 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE