

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/sal22-t-k-durbal>



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]					
right hand thread	left hand thread	A	G	B	C ₁	d ₂	
SA L22 T/K		22	M 22 x 1,5	28	20,00	54	
type	i ₁ min	measurement [mm]		h	α [°]	Tragzahlen C ₀ [kN]	weight [kg]
SA / SA L22 T/K	48	27	84	15		68,0	0,480

Merk	DURBAL
N° Ean13	3663952490250
Binnendiameter	22 mm
Buitendiameter	54 mm
Dikte	28 mm
Type	SA
Gewicht	480 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE