

SA Stangkop DSSAL5-T-K-DURBAL - SSAL5-T-K-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/ssal5-t-k-durbal>

DSSAL5-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C1	d2
DSSAL 5 T/K		5	M 5	8	6,00	18

type	measurement [mm]			load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂ min	h		
DSSA / DSSAL 5 T/K	19		33	6,0	0,013

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952490564
Binnendiameter	5 mm
Buitendiameter	18 mm
Dikte	8 mm
Type	SA
Gewicht	13 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE