

SA Stangkop SSA16-T-K-DURBAL - SSA16-T-K-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/ssa16-t-k-durbal>

SSA16-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number | right hand thread | left hand thread | measurement [mm] | | | |
|--------------|-------------------|------------------|------------------|----|-------|----|
| SSA 16 T/K | 16 | | M 16 | 21 | 15,00 | 42 |

| type | measurement [mm] | | | alpha [°] | load rating C ₀ [kN] | weight [kg] |
|-------------------|------------------|--------------------|----|-----------|---------------------------------|-------------|
| | i, min | i ₂ min | h | | | |
| SSA / SSAL 16 T/K | 37 | 21 | 66 | 15 | 39,0 | 0,210 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | DURBAL |
| N° Ean13 | 3663952490786 |
| Binnendiameter | 16 mm |
| Buitendiameter | 42 mm |
| Dikte | 21 mm |
| Type | SA |
| Gewicht | 210 g |
| Draad | Rechtse draad |
| Smering | zonder |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE