

SI Stangkop DSSIL6-T-K-DURBAL - DSSIL6-T-K-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/dssil6-t-k-durbal>

DSSIL6-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 6 T/K			d	G	B	C ₁	d ₁	d ₂	d ₃	d ₄
			6	M 6	9	6,75	20	10,0	13	

type	measurement [mm]				α °FS	load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h				
DSSIL / DSSIL 6 T/K	12	11	30	13	7,7	0,022	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952491097
Binnendiameter	6 mm
Buitendiameter	20 mm
Dikte	9 mm
Type	SI
Gewicht	22 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE