

SI Stangkop DSSIL10-T-K-DURBAL - DSSIL10-T-K-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/dssil10-t-k-durbal>

DSSIL10-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K,
in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


rod end body:
stainless steel

Sliding combination:
steel / bronze-PTFE composite

inner ring:
stainless steel, hardened and ground

Outer ring:
stainless steel body pressed around,
outer race lined with bronze-PTFE composite

Lubrication:
maintenance free



order number	right hand thread	left hand thread	measurement [mm]						
DSSIL 10 T/K			d	G	B	C ₁	d ₁	d ₂	d ₃
			10	M 10	14	10,50	28	15,0	19

type	measurement [mm]			α	load rating	weight
	l _s min	W	h	°	C ₀ (kg)	kg
DSSIL / DSSIL 10 T/K	20	17	43	13	18,0	0,077

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952491172
Binnendiameter	10 mm
Buitendiameter	28 mm
Dikte	14 mm
Type	SI
Gewicht	77 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE