

SI Stangkop DSSIL12-T-K-DURBAL - DSSIL12-T-K-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/dssil12-t-k-durbal>

DSSIL12-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number | right hand thread | left hand thread | measurement [mm] | | | | | | | |
|--------------|-------------------|------------------|------------------|------|----|-------|----|------|----|----|
| DSSIL 12 T/K | | | d | G | B | C1 | d1 | d2 | d3 | d4 |
| | | | 12 | M 12 | 16 | 12,00 | 32 | 17,5 | 22 | |

| type | l1 min | W | h | α | load rating C0 [kN] | weight [kg] |
|---------------------|--------|----|----|----|---------------------------|----------------|
| DSSi / DSSIL 12 T/K | 22 | 19 | 50 | 13 | 24,0 | 0,100 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | DURBAL |
| N° Ean13 | 3663952491264 |
| Binnendiameter | 12 mm |
| Buitendiameter | 32 mm |
| Dikte | 16 mm |
| Type | SI |
| Gewicht | 100 g |
| Draad | Linkse draad |
| Smering | zonder |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE