

SI Stangkop SSIL16-T-K-DURBAL - SSIL16-T-K-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/ssil16-t-k-durbal>

SSIL16-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
SSIL 16 T/K			d	G	B	C ₁	d ₁	d ₂	d ₃	d ₄
			16	M 16	21	15,00	42	22,0	27	

type	l ₁ min	W	h	α	load rating C ₀ [kN]	weight [kg]
SSI / SSIL 16 T/K	28	22	64	15	39,0	0,220

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952491417
Binnendiameter	16 mm
Buitendiameter	42 mm
Dikte	21 mm
Type	SI
Gewicht	220 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE