

# SA Stangkop GAR20-UK-2RS-DURBAL - GAR20-UK-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/gar20-uk-2rs-durbal>


## GAR20-UK-2RS



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	measurement (mm)		measurement (mm)		load rating		weight
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	C <sub>0</sub> (kN)	(kg)
GAR 20 UK (-2RS)		20	M 20 x 1,5	16	13,0		53
type	l <sub>1</sub> min	l <sub>2</sub> min	h	a [°]	load rating	weight	
GAR / GAL 20 UK-2RS	43	27	78	9	60,0	0,310	

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952493060
Binnendiameter	20 mm
Buitendiameter	53 mm
Dikte	16 mm
Type	SA
Gewicht	310 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE