

SA Stangkop GAR25-UK-2RS-DURBAL - GAR25-UK-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/gar25-uk-2rs-durbal>

GAR25-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	d	G	measurement (mm)	B	C1	d2
right hand thread						
left hand thread						
GAR 25 UK (-2RS)	25	M 24 x 2	20	17,0	64	

type	l, min	measurement (mm)	h	α [°]	load rating C_0 [kN]	weight (kg)
GAR / GAL 25 UK-2RS	53	32	94	7	83,0	0,560

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952493176
Binnendiameter	25 mm
Buitendiameter	64 mm
Dikte	20 mm
Type	SA
Gewicht	560 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE