

SA Stangkop GAR30-UK-2RS-DURBAL - GAR30-UK-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/gar30-uk-2rs-durbal>

GAR30-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	d	g	measurement (mm)	C1	d2
right hand thread	30	M 30 x 2	22	19,0	73
left hand thread					
GAR 30 UK (-2RS)					

type	l, min	measurement (mm)	h	a	load rating	weight
GAR / GAL 30 UK-2RS	65	37	110	6	C ₀ (kN) 110,0	(kg) 0,890

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952493220
Binnendiameter	30 mm
Binnendiameter	1.181" inch
Buitendiameter	73 mm
Buitendiameter	2.874" inch
Dikte	22 mm
Dikte	0.866" inch
Type	SA
Gewicht	897 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE