

# GE Stangkop GAR50-UK-2RS-DURBAL - DGAR50-UK-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/dgar50-uk-2rs-durbal>


## GAR50-UK-2RS



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	measurement (mm)		measurement (mm)		load rating		weight
right hand thread	d	G	B	C1	C0	(kN)	(kg)
<b>GAR 50 UK-2RS</b>	50	M 45 x 3	35	30,0		290,0	3,400

type	l, min	measurement (mm)	h	alpha	load rating	weight
		l, min		[°]	(kN)	(kg)
GAR / GAL 50 UK-2RS	107	60	185	6	290,0	3,400

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3616060467737
Binnendiameter	50 mm
Buitendiameter	112 mm
Dikte	35 mm
Type	GE
Gewicht	3400 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1
Standaard	Geen standaard

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE