

GE Stangkop

GAR50-UK-2RS-DURBAL - GAR50-UK-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/gar50-uk-2rs-durbal>


GAR50-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	measurement (mm)					
right hand thread	left hand thread	d	G	B	C ₁	d ₂
GAR 50 UK-2RS		50	M 45 x 3	35	30,0	112

type	measurement (mm)			load rating C ₀ (kN)	weight (kg)	
	l, min	h	α [°]			
GAR / GAL 50 UK-2RS	107	60	185	6	290,0	3,400

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3616060467737
Binnendiameter	50 mm
Buitendiameter	112 mm
Dikte	35 mm
Type	GE
Gewicht	3400 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE