

SI Stangkop GIL10-UK-DURBAL - GIL10-UK-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/gil10-uk-durbal>

GIL10-UK



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number right hand thread	measurement [mm]		measurement [mm]				
	d	G	B	C ₁	C ₂	d ₂	d ₄
GIL 10 UK	10	M 10	9	7,0	29	15,0	19
type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]	
	l ₃ min	h	W				
GIR / GIL 10 UK	20	43	17	12	17,6	0,061	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952493657
Binnendiameter	10 mm
Buitendiameter	29 mm
Dikte	9 mm
Type	SI
Gewicht	61 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE